CRESTO SAFETY

RESQ SOLO X+ TECH

IQDX+

- Lightweight
- Reliable
- Rescue ready

Standards: EN 341 : 2011 | ANSI Z359.4-2013

Product description

Your pocket-sized lifesaver
RESQ Solo X is a new high-spec, easy to use personal automatic evacuation device with rope lock that delivers maximum safety with minimum fuss in a specially designed bag for great ergonomic.

Smallest and most lightweight on the market
RESQ Solo X+'s size is equivalent to an iPhone and the lightweight kit is comparable to a laptop, making it as comfortable as possible to carry every day without becoming a burden. A line that is only 4,8 mm in diameter and only weighing 16.5g/m makes the whole kit extremely lightweight – and surprisingly compact when packed.

Perfect for the Wind Industry, Cranes and Utility businesses
Built to evacuate people weighing up to 141 kg from a maximum height of 300 meters, the steel centrifugal brake system and the braided Twaron aramid rope, which is heat resistant to 450°C, work together to ensure a safe and controlled descent.

Maximum safety. Minium fuss
An integrated swivel reduces the risk of rope twist during use, and together with the coreless rope reduces the risk of "ghost knots", contributing to a safer descent. The new centrifugal brake system offers improved safety and control during the descent, which is a crucial factor for the user's confidence, safety and well-being.

Designed & made for Nordic climates – safe for global use
The RESQ Solo X+ has been designed and adapted to allow controlled descents in challenging environments and is certified for use at -40 degrees to +60 degrees.

RESQ Solo X+ is equipped with a rope lock that enables simple rescue with a lifting accessory.

Product properties

ProductPdfTemplate:	Cresto Safety Product PDF
Brand:	RESQ
Material:	Aluminum , Steel, Aramid
Min/Max load (kg):	30/141
Minimum load (kg):	30
Maximum load (kg):	141
Maximum number of users:	1
Min/Max working temperature (c):	-40/+60

Minimum working temperature (c):	-40
Maximum working temperature (c):	60
EN-standard:	EN 341 : 2011
Other standards:	ANSI Z359.4-2013
Notified body:	0511, AUVA, Allgemeine Unfallversicherungsanstalt Sicherheitstechnische Prüfstelle - Wienerbergstrasse 11 1100 Wien, Austria
Annual inspection:	Yes, every 12 months
Life span:	15 + 15 years. Product lifecycle 15 years + 15 after service
RFID:	Yes
Warranty:	2 year
Declaration of Conformity:	Yes
Rope:	4,8mm TWARON Aramide hollow core braided rope
Maximum rope length (m):	300
Maximum descent:	1x300m
Descent speed (m/s):	0,5-2
Minimum breaking strength - MBS (kN):	14
Gate feature:	Twist lock
Gate opening (mm):	17
Gate strength (kN):	16
Attaching connector 1:	Steel carabiner
Functions:	Descend function
Mechanics:	Cetrifugal brake system
Adjustable under load:	Yes

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
08100224100	RESQ SOLO X+ Tech 100m	100	BLACK	7350015792043	Slovakia
08100224125	RESQ SOLO X+ Tech 125m	125	BLACK	7350015792050	Slovakia
08100224150	RESQ SOLO X+ Tech 150m	150	BLACK	7350015792067	Slovakia
08100224175	RESQ SOLO X+ Tech 175m	175	BLACK	7350015792074	Slovakia
08100224200	RESQ SOLO X+ Tech 200m	200	BLACK	7350015792081	Slovakia

08100224225	RESQ SOLO X+ Tech 225m	225	BLACK	7350015792098	Slovakia
08100224250	RESQ SOLO X+ Tech 250m	250	BLACK	7350015792166	Slovakia
08100224275	RESQ SOLO X+ Tech 275m	275	BLACK	7350015792173	Slovakia
08100224300	RESQ SOLO X+ Tech 300m	300	BLACK	7350015792180	Slovakia
08100224050	RESQ SOLO X+ Tech 50m	50	BLACK	7350015791992	Slovakia
08100224075	RESQ SOLO X+ Tech 75m	75	BLACK	7350015792036	Slovakia